

Competence creates Confidence.



- Model no. H3014-0013

## CIRCULATING AIR OVEN

ISO 2505

The circulating air oven is used to condition specimens according to the dimensional change of pipes and also as a drying oven (e.g. for determining the degree of crosslinking, water absorption, etc.).



### Standard features

- Operating convenience thanks to LCD display and membrane keypad
- Overtemperature protection
- Uniform temperature distribution in usable space
- High-quality oven insulation and insulated doors for minimum energy loss
- Digital temperature display
- High temperature accuracy
- Test chamber made from high-quality stainless steel
- CE conformity

### Version CIRCULATING AIR OVEN

H3014-0013

Max. operating temperature	°C	300
Spatial temperature constancy	°C	±1.0
Temporal temperature constancy	°C	±0.2
Temperature fluctuation	°C	±0.2
Usable space	l	230
Grid shelves		2
Data interface		Ethernet
Permissible ambient temperature	°C	+5 to +30
Permissible relative humidity	%	Max. 70 Non-condensing
Width (internal)	mm	592
Depth (internal)	mm	520
Height (internal)	mm	750
Width (external)	mm	965
Depth (external)	mm	670
Height (external)	mm	920
Weight	kg	90
Voltage data		230 V, 50/60 Hz Special voltages on request

### Accessories CIRCULATING AIR OVEN

Product	Description	Model no.
	Marking gauge	1291